

TechMaster

User instructions



Default codes

Master	1 2 3 4 5 6 7 8	
Manager	1 2 3 4 5 6 +	Optional Dallas key
User 2	0 2 - 0 2 0 2 0 2 +	Optional Dallas key
User 3	0 3 - 0 3 0 3 0 3 +	Optional Dallas key
User x	x x - x x x x x x +	Optional Dallas key

Dallas key

In the event that the user is composed of "code + Dallas key", before or after entering the code, the Dallas key must be placed on the appropriate Dallas key reader.

Override users

Override users open without waiting the time delay. In the default programming they are set in dual code opening but, upon request, the single opening mode can also be set.

Silent alarm

It is activated by increasing or decreasing the last digit by one number when entering the opening code.



Penalty

After four attempts to enter an incorrect code, the lock starts a 4-minute delay period. Each attempt to enter the code within the 4 minutes delay period restarts the count.

Low battery warning

A message on the display and a long beep during opening indicates a low battery level. Replace immediately the low battery with a new Alkaline battery.

Sound signals

A double beep  normally indicates a correct operation. A long beep  indicates an incorrect operation and the end of the operation itself.

Recommendations

Do not use easily identifiable codes such as 123456, dates of birth or other personal information.

Opening (It is recommended to change the factory code before use and to safely store the new code)

Press any key to turn on the device. The display shows the message:

USER CODE
X X - X X X X X X

Press  to open with Manager code or go to the next step.

MANAGER
X X X X X X

Enter the opening code. The display shows the time delay counting if programmed.

TIME DELAY
00:59

At the end of the time delay, the display shows the counting of the open window.

OPEN WINDOW
00:01

Enter the opening code. The display shows the message:

OPEN

Open the safe door within 4 seconds.

Dual code opening (It is recommended to change the factory code before use and to safely store the new code)

Press any key to turn on the device. The display shows the message:

USER CODE
X X - X X X X X X

Press  to open with Manager code or go to the next step.

MANAGER
X X X X X X

Enter the opening code. The display shows the time delay counting if programmed.

TIME DELAY
00:59

At the end of the time delay, the display shows the counting of the open window.

OPEN WINDOW
00:01

Enter the 1° opening code. The display shows the message:

2° USER CODE
X X - X X X X X X


Enter the 2° opening code. The display shows the message:

OPEN WINDOW

Open the safe door within 4 seconds.

Change code (Safely store the new code and perform various opening / closing tests before closing the safe door)

To be performed with the door open!

Press and hold . The display shows the message:

To change the Manager code press  twice. The display shows the message:

Enter the **old code**. The display shows the message:



Enter the **new code**. The display shows the message:

Confirm the **new code**.

Perform various opening / closing tests before closing the safe door.

Users management

Press  and then . The display shows the message:

Enter the Manager code and scroll through the submenus with  until Users management. Press  to access.

Press  to scroll the list or enter the user ID.

"✓" installed user, "X" disabled user, "_" deleted user.

Overrides users can be installed only when the lock is open.

Press . If the user is not installed, the display shows the message:

Press  to confirm, or  to disable/enable/delete and  to confirm.

Membrane test

Press any key to turn on the device.

Press and hold the button . The display shows the message:

Press in sequence the buttons shown in the display.


A confirmation beep is given for each pushed key working properly.


A damaged key is indicated with a long beep. The display shows the message:


Change date and time

Press (or press and hold) . The display shows the message:

Enter the Master code. The display shows the message:

Press . The display shows the date and time currently set:

To modify, press . The display shows the message:

Enter time and date and press  to confirm.

Further information

For the complete manual and further information on the product's features, please visit www.tecnosicurezza.it

OLD CODE X X - X X X X X X
CHANGE MANAGER CODE
NEW CODE X X X X X X
CONFIRM CODE X X X X X X
OPERATION DONE

MANAGER MENU X X X X X X
USERS MANAGEMENT
02 03 04 05 06 ✓ X - - ✓

02 INSTALL?

MEMBRANE TEST 1234567890 + ✓
MEMBRANE TEST 1234567890 + ✓

WRONG/FAULTY KEY

MASTER MENU X X X X X X X X
TIME AND DATE SETTINGS
12:00 WED 13 /02/2019
hh:mm _ _ _ _ DD/MM/YYYY

GLOBAL HEADQUARTERS
Tecnosicurezza SpA
Via Cesare Battisti. 276
37057 San Giovanni Lupatoto
Verona
Tel.+39 045 826 64 70
Fax. +39 045 826 64 69
info@tecnosicurezza.it

USA HEADQUARTERS
Tecnosicurezza Inc.
50, Thomas Lane
Versailles, KY 40383
Tel.+1 859 490 89 30
info@usatecno.com

SPAIN HEADQUARTERS
Tecnosicurezza Sa
C/Menor, 4 - Nave 10
Pol. Ind La Mina 28770
Colmenar Viejo
Tel.+34 91 804 33 91
Fax.+34 91 804 32 63
info@tecnosicurezza.es

