

PulsePro

PROFESSIONAL CONTROL FOR
HIGH-GRADE SECURITY



From retail networks managing safes across multiple store locations to banks and safe manufacturers, Pulse PRO delivers the advanced user management and audit capability that professional environments demand.



Metal keypad with rubber membrane:

Available in **satín chrome** with optional Dallas key reader, Pulse PRO maintains a professional appearance while delivering robust functionality across high-traffic commercial settings.

www.tecnosicurezza.it

All trademarks appearing in this brochure are property of their respective owners.
Tecnosicurezza reserves the right to modify the data in this brochure without notice.

Built for the environments where access needs to be governed, not just granted. A layered credential structure lets a bank assign distinct responsibilities across branches, tellers and cash-handling teams, while dual-mode opening enforces shared accountability.

Over 80 pre-programmed configurations adapt to your specific operational requirements. It is fully configurable from the keypad, eliminating the need for external programming devices or computers, enabling immediate on-site setup.

TECNOSICUREZZA
Locks & Security Systems

Masters, Managers, users and override users sit in a defined hierarchy, so responsibilities map cleanly onto a bank's organisational structure and onto a manufacturer's range of products.

Up to 8,000 events stored with time and date provide a complete, traceable record for security review and compliance.

A programmable time delay (1-99 min) and opening window (1-19 min) slow forced openings, with the delay set to match each location's risk profile.

Silent alarm, remote disable opening and bolt status output, alongside many other security features, keep security teams informed during emergencies and after hours.

More than 80 pre-programmed configurations are selectable directly from the keypad, letting technicians and production lines set each lock to specification on-site. SwingBolt, DeadBolt, LatchBolt and the MotorLock family let safe manufacturers standardise on one electronic platform across diverse safe and vault designs.

The Emergency Rescue Code gives authorised personnel controlled recovery paths without compromising security.

Dual mode requires two valid credentials to open, enforcing shared responsibility on high-value vaults and cash points.

Software and Documents



Keypad

- 10 alphanumeric keys
- Keypad test
- Red LED
- Buzzer
- Battery compartment
- Dallas key reader
- 80 configurations selectable from keypad

Lock

- 2 Masters
- 3 Managers
- 49 Users
- 10 Override users
- Expiration of codes
- Time delay 1 - 99 minutes
- Open window 1 - 19 minutes
- Silent alarm
- Remote disable opening or Remote time delay override
- Bolt status output
- Dual mode
- Penalty
- Hotel mode
- Audit trail of 8,000 events with time and date
- Emergency Rescue Code (ERC)
- Master reset
- Hardware reset
- Dallas key management

Power supply

- 9V alkaline battery
- Battery box
- Power adapter

Locks

- SwingBolt
- DeadBolt
- LatchBolt
- MotorLock
- Motor LatchBolt Lock
- MotorLock Push&Pull

Certifications



Klasse 2



Type 1